



# Product Information

## FORECAST

### Description

This product is a semi-buffable, metal crosslinked acrylic floor finish which dries to a beautiful luster. Scuffs are readily removed by buffing with a white pad.

This product will outwear most conventional floor finishes. It can be scrubbed repeatedly with a neutral cleaner without loss of gloss or appearance.

This product levels well and has excellent recoatability, insuring ease of application under all conditions.

**WARNING: WET FLOORS ARE SLIPPERY.** Use proper caution and display warning placards anytime floors are wet. This product is not recommended for exterior use or use on interior floors that are subject to standing water or wet conditions.

### Directions

1. Thoroughly clean the floor and remove all old wax or finish using a solution of a concentrated wax and finish stripper. Pay particular attention to corners and baseboards to ensure that all old coatings have been removed.
2. Scrub rinse well with clear water, pick up with a wet vac or mop and allow to dry.
3. Apply the finish using a lamb's wool applicator, gravity flow applicator or a rayon mop.
4. For optimum gloss and durability apply 3 or 4 coats. Be sure previous coat has been dry (tack free) at least 15 minutes before applying next coat.
5. Maintain by damp mopping with a neutral cleaner.
6. Recoat traffic lanes on an as required basis.
7. Scuff marks can be removed by buffing with a low speed machine and white pad.
8. For best results, dust daily with a properly treated mop.

**CAUTION:** Contains polymer emulsions. Undiluted product may cause eye irritation. Avoid contact with eyes. Do not take internally. **FIRST AID:** In case of contact, flush eyes with plenty of water for 15 minutes. If irritation persists, see a doctor.

KEEP OUT OF REACH OF CHILDREN    KEEP FROM FREEZING    FOR INDUSTRIAL & INSTITUTIONAL USE ONLY

### Specifications

Type product	Metallic-acrylic
Appearance	Milky, white
Percent solids	16.0 ± 0.5
pH (100%)	8.9 ± 0.2
Weight per gallon	8.44 lbs.
Freeze/thaw stability	3 cycles
Leveling	Excellent
Recoatability	Excellent
Gloss	Very good
Buffability	Semi-buffable
Heelmark resistance	Very good
Water resistance	Very good
Detergent resistance	Very good
Powdering resistance	Excellent
V.O.C.	198 gm/l
Coverage	2000 sq. ft. per gallon