



Product Information

SPRAY BACK

Description

This product is a ready to use, water based spray buff cleaner designed specifically for the maintenance of metal interlocked floor finishes. It's exclusive formula effectively cleans the surface, repairs scratches in the finish and leaves a bright shine.

The combination of cleaning ingredients quickly removes ground-in dirt and black marks. Special polymers heal scars in the finish and leave a brilliant mirror-like gloss.

One of the outstanding features of this product is it's relatively quick drying property which results in significant time savings. Use of the spray buff method will greatly reduce the cost of floor maintenance.

Recommended Uses

This product can be quickly and easily applied using a trigger spray bottle. It can be used to spray buff vinyl, vinyl composition, asphalt, rubber, linoleum, terrazzo and other masonry type floors.

WARNING: WET FLOORS ARE SLIPPERY.

Use proper caution and display warning placards anytime floors are wet. This product is not recommended for exterior use or use on interior floors that are subject to standing water or wet conditions.

Directions

To obtain best results from spray buffing, it is important to have a good floor finish base. A minimum of three to four coats are needed.

NOTE: Allow the floor finish to cure at least three days before spray buffing in order that maximum hardness can be obtained. Spray buffing too soon after application can result in dulling the finish.

1. Sweep or dust mop floor to remove loose soil. If heavy soiling is present, damp mop with a neutral cleaner.
2. Fill a trigger spray bottle with this product as it comes from the container. DO NOT DILUTE. Apply a fine mist to a section 3 x 6 ft.
3. Buff with machine using pads recommended for spray buffing. Inspect pads periodically to determine if soil is building up on pad; if so, change pad. Spray buff until floor area is dry and shining.
4. Dust mop with properly treated dust mop to remove any soil that did not stick to the pad.

CAUTION: Contains polymer emulsions. Undiluted product may cause eye irritation. Avoid contact with eyes. Do not take internally. FIRST AID: In case of contact, flush eyes with plenty of water for 15 minutes. If irritation persists, see a doctor.

KEEP OUT OF REACH OF CHILDREN KEEP FROM FREEZING FOR INDUSTRIAL & INSTITUTIONAL USE ONLY

Specifications

Type product	Spray buff polymer
Appearance	Opaque pink
Viscosity (Gardner-Holdt tube)	Less than A-1
Percent solids	2.0 ± 0.5
Weight per gallon	8.35 lbs.
pH	8.6 ± 0.4
Oven stability	Over 30 days at 120° F
Flash point	None
Resistance to abrasion	Very good
V.O.C.	222 gm/l