



Product Information

BREAK DOWN

Description

This product is a highly concentrated cleaner, stripper and degreaser. It provides the extra strength necessary for the toughest cleaning jobs. In addition, the long dilutions provide the economy necessary to meet tight maintenance budget requirements.

This product tackles the toughest jobs, even in heavy traffic areas where soil level is greatest. Specifically formulated for industrial and commercial use to penetrate, lift and dissolve greasy soil and multiple coats of floor finish or wax. In lower concentrations it can be used to remove the greasy and smokey deposits on range hoods, filters and exhaust fans. In addition, it cleans all surfaces such as walls, tile, vinyl, fiberglass, concrete, terrazzo and sealed wood.

Superior wetting, penetrating and emulsifying agents provide effective action in all cleaning operations. It is nonflammable, contains no chlorinated solvents and gives off no toxic fumes. It is also biodegradable and phosphate free.

This product contains a special amine, which is sometimes called odorless ammonia. It acts as effectively as ammonia without the offensive odor. This is a controlled suds product and may be used in automatic scrubbers; foam level is held down so premature cut-off of the vacuum does not occur.

Recommended Uses

For heavy duty wax and finish stripping; degreasing ovens, hoods, ranges, fans . . . also for cleaning walls, tile, vinyl, fiberglass, concrete, terrazzo and sealed wood.

Directions

NOTE: Do not use on unsealed marble or terrazzo unless tested at use dilution in an inconspicuous area to determine if staining or other damage occurs.

The use ratios given below are approximate. They may have to be varied according to soiling conditions and the type of equipment used. Always test diluted product in an inconspicuous area for floor surface effect to determine suitability for use.

1. For heavy duty cleaning of concrete floors using an automatic scrubber or single disc machine, use as a starting point 12 ounces of this product per gallon of water.
2. For normal soiling conditions use 8 ounces per gallon of water.
3. For lightly soiled floors, use 4 ounces per gallon of water.
4. When using an automatic scrubber, spread the solution on the first pass, and allow to stand for a few minutes. Scrub and pick up on second run.

For Wax Stripping

1. Prepare a stripping solution using 12 ounces of this product per gallon of water.
2. Apply solution liberally and be certain surface is completely covered.
3. Allow solution to remain on surface for 5 minutes or longer. (Do not allow stripper solution to dry on the floor.)
4. Machine scrub with proper pad.
5. Pick up solution with a mop or wet vac.
6. Flood rinse well with clear water and pick up with wet vac or mop.

ATTENTION: Avoid contact with glass. If this product is allowed to dry on glass, a residue will be created which may not be removable. If accidentally splashed on glass, flush immediately with water before the product dries.

WARNING: CONTAINS ALKALINE SILICATES, SURFACTANTS, AND GLYCOL ETHER SOLVENTS. SKIN AND EYE IRRITANT. Contains Alkaline Silicates, Surfactants, and Glycol Ether Solvents. Do not get in eyes, on skin or clothing. Harmful if swallowed. Do not take internally.

FIRST AID: For eyes, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin, wash thoroughly with water. If irritation persists, see a doctor. If swallowed, drink large quantities of water or milk. Get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN KEEP FROM FREEZING FOR INDUSTRIAL & INSTITUTIONAL USE ONLY

BREAK DOWN

Specifications

Type product	High activity stripper/degreaser
Weight per gallon	8.80 lbs.
Percent solids	12.0 ± 1.0
Percent active	25.0 ± 1.0
Color	Blue
Freeze/thaw stability	Passes 3 cycles
pH	13.0 ± 0.5
Solubility in water	Complete
Coverage (12 oz./gal.)	2200 sq. ft. per gal.