



Product Information

BLACK SHOWCASE

Description

This product is a metal cross-linked black pigmented floor finish specifically formulated for use on black asphaltic tile found typically in post offices and other governmental institutions.

The special acrylic polymers used produce the ultimate in floor finish durability, thereby minimizing maintenance.

It also responds beautifully to a spray buff or light burnishing maintenance program.

WARNING: WET FLOORS ARE SLIPPERY. Use proper caution and display warning placards anytime floors are wet. This product is not recommended for exterior use or use on interior floors that are subject to standing water or wet conditions.

Directions

NOTE: Mix this product thoroughly before use.

1. Thoroughly clean the floor and remove all old wax or finish using a solution of a concentrated wax and finish stripper. Pay particular attention to corners and baseboards to ensure that all old coatings have been removed.
2. Rinse well with clear water and allow to dry.
3. Apply the finish using a lamb's wool applicator, gravity flow applicator or a rayon mop.
4. For optimum gloss and durability apply 3 or 4 coats. Be sure previous coat is "tack free" before applying next coat.
5. Maintain by damp mopping with a neutral cleaner.
6. Recoat traffic lanes on an as required basis.
7. Spray buffing with a material designed for this type maintenance will restore gloss.
8. For best results, dust daily with a properly treated mop.

CAUTION: Contains polymer emulsions. Undiluted product may cause eye irritation. Avoid contact with eyes. Do not take internally.

FIRST AID: In case of contact, flush eyes with plenty of water for 15 minutes. If irritation persists, see a doctor.

KEEP OUT OF REACH OF CHILDREN KEEP FROM FREEZING FOR INDUSTRIAL & INSTITUTIONAL USE ONLY

Specifications

Type product	Metallic-acrylic
Appearance	Opaque black
Percent solids	18.0 ± 0.2
pH (100%)	8.0 - 8.4
Weight per gallon	8.57 lbs.
Freeze/thaw stability	Passes 3 cycles
Leveling	Excellent
Recoatibility	Excellent
Gloss	Excellent
Buffability	Nonbuffable
Heelmark resistance	Very good
Water resistance	Very good
Detergent resistance	Good
Powdering resistance	Excellent
Coverage	1800 - 2000 sq. ft. per gallon
V.O.C.224 gm/l