



Product Information

APPLAUSE

Description

This product is designed specifically for high speed burnishing. Its combination of acrylic resin fortified with durable urethane provides a long wearing film that responds readily to high speed burnishing.

This product provides a clear film which will not discolor with aging and exhibits excellent mark and scuff resistance. It has outstanding detergent and water resistance but can be removed with an amine based stripper.

Recommended Uses

This product is recommended for all resilient tile including asphalt, vinyl, vinyl composition, rubber, linoleum, terrazzo, and other masonry surfaces. It is ideally suited for heavy traffic areas such as supermarkets, shopping malls, restaurants, retail stores and office buildings.

WARNING: WET FLOORS ARE SLIPPERY. Use proper caution and display warning placards anytime floors are wet. This product is not recommended for exterior use or use on interior floors that are subject to standing water or wet conditions.

Directions

1. Remove all old wax and finish using an amine stripper. Pick up stripper solution with a wet vacuum.
2. Scrub rinse with clear water and allow floor to dry thoroughly.
3. Apply this product with a rayon mop or gravity fed applicator.
4. Allow to dry until "tack free" and apply a second coat. Apply a total of four coats.

Maintenance

1. Dust mop daily with mop treated with a water based dust mop product.
2. Damp mop as required with a neutral cleaner.
3. Burnish weekly, or more often if necessary, with a 1500 rpm machine and high speed burnishing pad.
4. When required, a restorer product can be used to enhance the gloss.

COVERAGE: 2000 sq. ft./gal.

CAUTION: Contains polymer emulsions. Undiluted product may cause eye irritation. Avoid contact with eyes. Do not take internally.

FIRST AID: In case of contact, flush eyes with plenty of water for 15 minutes. If irritation persists, see a doctor.

KEEP OUT OF REACH OF CHILDREN KEEP FROM FREEZING FOR INDUSTRIAL & INSTITUTIONAL USE ONLY

Specifications

Type product	Urethane/acrylic floor finish
Percent solids	17.0
pH	9.1 ± 0.5
Appearance	Opaque white
Viscosity (Gardner-Holdt tube)	Less than A-1
Weight per gallon	8.53 lbs.
Drying time (normal conditions)	30 - 45 minutes
Freeze/thaw stability	Passes 3 cycles
Flash point	None
Resistance to cold water (48 hour dry)	Excellent
Resistance to abrasion	Excellent
Removability	Amine type stripper
Washability	Excellent
Application	Gravity fed applicator or rayon mop
V.O.C.	248 gm/l
Coverage	2000 sq. ft. per gallon