



Product Information

SEAL REMOVER

DESCRIPTION

This product does not contain METHYLENE CHLORIDE. The residue of this product, and the film it has removed, is considered hazardous waste, and special disposal methods are required. It is formulated with materials which can be used without taking extraordinary precautions. Because of the low vapor pressure it does not pose an explosion or inhalation hazard. In addition, this product is completely miscible with water and biodegradable.

This product is ideal to use on wood, concrete and other masonry floors for removing old seals, gym finish, shellac, varnish or lacquer. It can be used to remove a variety of seals, including urethanes, epoxies, acrylics, chlorinated polymers, and water-based coatings. It will also remove polyester and polyvinyl chloride adhesive residue. It also removes epoxy grout haze from ceramic tile.

Coverage will vary from 50-120 sq. ft. per gallon. For heavy duty stripping of multiple coats of old seals, on rough surfaces, coverage will be 50 sq. ft. per gallon.

DIRECTIONS

CONCRETE SURFACES

1. Pour a ribbon of this product on the floor Spread liberally, using a lamb's wool applicator. Apply to an area approximately 3 ft. wide to avoid stepping in stripper solution when machine scrubbing.
2. Allow to stand 20 to 45 minutes, or until old seal is softened and loosened from surface.
3. Scrub with single disc floor machine and steel wire brush.
4. Squeegee old seal and shovel into plastic 5 gallon pail or metal container for special waste disposal.
(NOTE: A second application may be required for multiple coats of aged films and high performance type coatings.)
5. Scrub stripped area with a solution of a heavy-duty stripper/degreaser. Pick up cleaning solution with wet vacuum or flush down drain.
6. To remove cleaner residue, scrub/rinse with a rinsing aid. Scrub rinse with clear water.
7. Allow to dry thoroughly before applying a coating.

WOODSURFACES

IMPORTANT: Remove painted areas from gymnasium floors first to prevent discoloring wood. Apply stripper over lines with a brush and allow to stand for 20-45 minutes, then scrape with putty knife.

1. Pour a ribbon of this product on the floor and spread liberally, using a lamb's wool applicator. Apply to an area approximately 3 ft. wide to avoid stepping in stripper solution when machine scrubbing.
2. Allow to stand 20 to 40 minutes, or until old seal is softened and loosened from surface.
3. Scrub with single disc floor machine and steel wire brush.
4. Squeegee old seal and shovel into plastic 5 gallon pail or metal container for special waste disposal.
(NOTE: A second application may be required for multiple coats which are aged.)
5. Apply waterless cleaner and scrub with a single disc machine and black pad. Pick up cleaner residue with towels or wet vacuum. Allow to dry.
6. If grain of wood is raised, abrade with 100-grit screen. Sweep or vacuum then tack floor with a waterless cleaner.
7. Allow floor to dry thoroughly before applying seal.

DISPOSAL

Used product intended to be discarded must not be disposed of as ordinary waste. Consult your local waste disposal or recycling service and MSDS for proper disposal.

WARNING: Eye And Skin Irritant. Contains N-methyl pyrrolidone and n-butoxy propanol. Avoid prolonged or repeated contact with skin. Do not take internally. FIRST AID: If in eyes, flush with water for at least 15 minutes. If irritation develops, see a doctor immediately. If on skin, wash with soap and water. If too much inhaled, move to fresh air. If swallowed, drink large quantities of water. Do not induce vomiting. See a doctor immediately.

Keep Out Of Reach Of Children For Industrial & Institutional Use Only

Specifications

Type product	Water soluble
Appearance	Light yellow, clear
Odor	Mild
Weight per gallon	8.55
Viscosity (cps).	200 + 50