

Product Information

TILE PROTECTOR

Description

Tile Star Tile Protector is an aqueous, fluorochemical, waterborne dispersion that provides a durable, transparent protective barrier against oil and water on mineral, porous masonry and concrete surfaces. This product provides a natural look and does not contain any silicone/wax components. Durable protection is provided with no effect on appearance.

Recommended Uses

This product is a low VOC waterproof coating for brick, grout, concrete, terra cotta, sanstone, decorative tiling, gypsum dry wall and other porous or mineral surfaces. In addition, Tile Protector is a low VOC oil proof coating for driveways, vehicle bays, industrial flooring, aircraft hangers, kitchen tiling and other surfaces continuously stained by oil.

Directions

Apply Tile Protector to clean and dry surfaces only. For maximum results, apply at full strength (never dilute), using a roller, sponge or paint pad. Make sure that the surface is completely covered. On new or porous surfaces a second coat may be desired. It is recommended that it be applied at right angles to the first application.

Use liberally but do not puddle and remove excess immediately. Allow ample time for the first coat to dry before the second application. Tools, applicators and hands can be cleaned with water. Since this product is a penetrating sealer, an application of Tile Star High Gloss Dressing or Matte Finish Sealer may be applied to enhance the surface. Tile Protector will last for many years before it is necessary to consider another application.

CAUTION: Eye Irritant. Do not get in eyes, on skin or clothing. Harmful if swallowed. Do not take internally. Do not spray with high pressure or aerosolizing spray since breathing of mist is harmful.

FIRST AID: For eyes - flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin - wash thoroughly with water. If irritation persists, see a doctor. If swallowed - DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

KEEP OUT OF REACH OF CHILDREN KEEP FROM FREEZING

Specifications

Type product	Aqueous fluorochemical dispersion
pH	4.0 to 6.0
Appearance	Clear, colorless
Weight per gallon	8.36 lbs.
Viscosity (cps)	<25 at 25° C
Flash point	>93° C (200°F) Pensky Martens closed cup
Stability	Minimum one year under normal conditions. Freeze/thaw stable; bring to room temperature and stir before using
VOC	50 g/L (EPA Test Method 24)
Coverage	600 - 1000 sq. ft. per gallon